LAMINAM®

CE

Declaration of performance

No. 001DoP-3mm-170215

1. **Unique identification code of the product type**: Dry-pressed ceramic tiles with water absorption $E_b \leq 0,5\%$; nominal thickness 3 mm.
2. **Intended uses**: For internal and external walls.
3. **Manufacturer**: Laminam S.p.A. via Ghiarola Nuova, 258 – 41042 Fiorano Modenese (MO) – Italy.
4. **System of AVCP**: System 4.
5. **Harmonized standard:** EN 14411:2016
6. **Declared performances**:

Essential characteristics	Performance
Name	Laminam 3
Reaction to fire	A1
Release of dangerous substance, for:	
– Cadmium	NPD
– Lead	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2S1/C2S2	1 N/mm^2
Thermal shock resistance	Pass
Durability for:	
– Internal use	Pass
– External use: freeze-thaw resistance	Pass

The performance of the product identified above is in conformity with the set of declared performances.
This declaration of performance is issued, in accordance with Regoulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Roberto Pederzoli, Quality Manager

Fiorano Modenese, 15 February 2017

Signature

www.laminam.it

Laminam S.p.A Società sottoposta all'attività di direzione e coordinamento ai sensi dell'art. 2497 e seguenti C.C., della società iscritta al registro delle imprese di Modena al n. 02438830362
Sede Legale e Operativa: Via Ghiarola Nuova 258 - 41042 Fiorano Modenese (Mo) Italy T. +39 0536 1844200 F. +39 0536 1844201 cap. soc. € 7.200.000 R.E.A. 332793 C. F. + P. IVA 01969990355